

SR-30

The SR-30 is the companion two channel RPU receiver to the SRPT-30 RPU transmitter. This two channel receiver can be operated anywhere within its specified operating band. No minimum spacing requirement within the band of operation. This receiver is available in bands from 135 to 965 MHz. Exact bands are shown below in the specifications section.



SR-30 Specifications

AC Input: 85 to 264VAC; 47-63Hz. **DC Input:** +10 to +14VDC.

ENVIRONMENTAL

Operating Temperature: -10°C to $+50^{\circ}\text{C}$.

 Humidity:
 5 to 95% RH, non-condensing.

 Frequency Range:
 SR-30-150
 135-185 MHz

 SR-30-230
 215-250 MHz

 SR-30-230
 215-250 MHz

 SR-30-250
 235-265 MHz

 SR-30-330
 300-350 MHz

 SR-30-450
 430-480 MHz

 SR-30-950
 935-965 MHz

Frequency Stability: $\pm 0.0001\%$, -20°C to +50°C.

Frequency Programming: Increment 1 Hz.

Accuracy: ±0.00025% of center frequency.

Change time: Less than 2 seconds.

Selectivity:

60dB (Bandwidth, kHz) Filter 3dB F250 220 F200 200 570 F85 85 145 F50 50 100 F36 36 60 F25 25 42

15

Spurious Response: -80d

Sensitivity: 0.5 microvolts for 20dB signal-to-noise. 2 microvolts

for 30dB signal-to-noise. $\overset{\cdot}{4}$ microvolts for 40dB signal-to-noise. 100 microvolts for maximum signal-to-noise, typically 57dB or greater.

AUDIO

Output Level: 0 to +12 dBm.

Output Impedance:15 Pin D-Type - Balanced, 600 ohms.Frequency Response:±1.5dB of the specified bandwidth.THD + Noise:2% or less of the specified bandwidth.S/N Ratio:36 kHz BW @ 5.4 kHz Dev 25 kHz BW @ 3.6 kHz Dev 53dB; 10 kHz BW @ 1.2 kHz Dev 44dB.

IMD: 75dB for 20dB signal-to-noise.

Image Rejection: 100dB.

HEADPHONE (Control @ Midrange)

Frequency Response: $\pm 1.5 dB$ of the specified bandwidth.

S/N Ratio: -37dB.

THD + Noise: 2.5% or less @ 400 Hz.

Channel Bandwidth: 50kHz, 36kHz, 25kHz, 20kHz TSL systems; 10kHz

FCC Emission Designator: 50KOF3E @ 36 or 50kHz Channel BW;

25KOF3E @ 25kHz Channel BW; 10KOF3E @ 10kHz Channel BW.

Dimensions: 3.5" H x 11.5" W x 14.3" D. (8.89 cm H x 29.21 cm W x

36.83 cm D).

Boxed Dimensions: 22" H x 19" W x 9" D. (55.88 cm H x 48.26 cm W x

22.86 cm D).

Weight: Net 7 lbs. (3.18 Kg) Packed 14 lbs (6.35 Kg).





